



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/523,954	08/18/2005	Michele Cassol	U 015593-6	9416
140 7590 09/29/2009 LADAS & PARRY LLP 26 WEST 61ST STREET NEW YORK, NY 10023				
EXAMINER VOLZ, ELIZABETH J				
ART UNIT 3781		PAPER NUMBER		
NOTIFICATION DATE 09/29/2009		DELIVERY MODE ELECTRONIC		

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

Notice of the Office communication was sent electronically on above-indicated "Notification Date" to the following e-mail address(es):

nyuspatactions@ladas.com

Office Action Summary

Application No.

10/523,954

Applicant(s)

CASSOL ET AL.

Examiner

ELIZABETH VOLZ

Art Unit

3781

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --
Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

- 1) ☒ Responsive to communication(s) filed on 11 June 2009.
- 2a) ☒ This action is **FINAL**. 2b) ☐ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

- 4) ☒ Claim(s) 29-56 is/are pending in the application.
- 4a) Of the above claim(s) _____ is/are withdrawn from consideration.
- 5) ☐ Claim(s) _____ is/are allowed.
- 6) ☒ Claim(s) 29-56 is/are rejected.
- 7) ☐ Claim(s) _____ is/are objected to.
- 8) ☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☒ The drawing(s) filed on 08 February 2005 is/are: a) ☒ accepted or b) ☐ objected to by the Examiner.
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

- 12) ☒ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☒ All b) ☐ Some * c) ☐ None of:
1. ☒ Certified copies of the priority documents have been received.
 2. ☐ Certified copies of the priority documents have been received in Application No. _____.
 3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

* See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

- 1) ☐ Notice of References Cited (PTO-892)
- 2) ☐ Notice of Draftperson's Patent Drawing Review (PTO-948)
- 3) ☒ Information Disclosure Statement(s) (PTO-8508)
Paper No(s)/Mail Date 6/15/09
- 4) ☐ Interview Summary (PTO-413)
Paper No(s)/Mail Date _____
- 5) ☐ Notice of Inventor's Patent Application
- 6) ☐ Other: _____

DETAILED ACTION

Claim Rejections - 35 USC § 103

1. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

2. Claims 29-45 and 51-56 are rejected under 35 U.S.C. 103(a) as being unpatentable over Thorp (U.S. Patent No. 3,701,454) in view of Jacke (U.S. Patent No. 3,435,977).
3. Regarding Claim 29, Thorp discloses a fuel can 10 (Figure 1) with a can body 12 (Figure 1) containing a fuel filling 32 (Figure 2) and a cover lid 16 (Figure 1) which is formed by a sealing foil and which by sealing onto a flange like rim 22 (Figure 2) of the can body is firmly connected to the can body, wherein that the cover lid is designed in such a manner that at least one opening (Figure 3) in the cover lid is producible by a complete of partial severing of detaching of one or more lid portion elements along one of several material bonded predetermined breaking locations (Figure 3). Thorp does not disclose a sealing layer comprising at least two metal foils interconnected by a synthetic material layer located between same, and in particular, whereby the metal foils are aluminum foils, which are interconnected with each other by a polyethylene layer. However, Jacke teaches two aluminum foils 30/31 (Figure 3) interconnected by a

polyethylene layer 32 (Figure 3; Column 3, Lines 5-8). Therefore, it would have been obvious for one of ordinary skill in the art at the time the invention was made to modify Thorp to include two aluminum foils interconnected by a polyethylene layer, as taught by Jacke, in order to strengthen the cover lid while reducing metal required (Column 1, Lines 38-43).

4. Regarding Claims 30 and 31, Thorp teaches all the limitations substantially as claimed except for a first metal foil weakened along a predetermined breaking location whereas a second metal foil is continuous in the area of the predetermined breaking location and the second metal foil faces the can body. However, Jacke teaches a first metal foil 31 (Figure 3) weakened 42 (Figure 3) along a predetermined breaking location whereas a second metal foil 30 (Figure 3) is continuous in the area of the predetermined breaking location and the second metal foil faces the can body.

Therefore, it would have been obvious for one of ordinary skill in the art at the time the invention was made to modify Thorp to include a first metal foil weakened along a predetermined breaking location whereas a second metal foil is continuous in the area of the predetermined breaking location and the second metal foil faces the can body, as taught by Jacke, in order to assist in the removal of the tab.

5. Regarding Claim 32, Thorp discloses a severable lid portion element which remains undetachably connected at the cover lid (Figure 5).

6. Regarding Claim 33, Thorp discloses part of the severable lid portion elements which are designed as peel-off elements 58 (Figure 5), and in particular, in that they are formed by a peel-off foil element extending across the entire cover lid (Figure 5).

7. Regarding Claim 34, Thorp discloses part of a severable lid portion element is designed as a sub-area 40 (Figure 1) which is detachable from the cover lid.
8. Regarding Claim 35, Thorp discloses that by severing lid portion elements, various openings are selectively producible in the cover lid (Figure 5). Examiner believes "producible" means "capable of being produced".
9. Regarding Claim 36, Thorp discloses a pulling ring 60 (Figure 5) which projects over an outer border of the fuel can in order to facilitate a severing of a lid portion.
10. Regarding Claim 37, it would have been an obvious matter of design choice to modify Thorp to have openings with an opening pattern with at least two axes of symmetry, since applicant has not disclosed that having symmetric openings solves any stated problem or is for any particular purpose and it appears that the device would perform equally well with either designs.

Furthermore, absent a teaching as to criticality of the openings having at least two axes of symmetry, this particular arrangement is deemed to have been known by those skilled in the art since the instant specification and evidence of record fail to attribute any significance (novel or unexpected results) to a particular arrangement. In re Kuhle, 526 F.2d 553,555,188 USPQ 7, 9 (CCPA 1975).

11. Regarding Claim 38, Thorp discloses a center opening in the cover lid which is substantially the same shape as the surface of a fuel filling in the can body (Figure 5).
12. Regarding Claim 39, Thorp discloses a substantially circular or quadratic center opening is producible, and in particular, in that it comprises an area which corresponds to at least 15% of the surface area (Figure 5).

13. Regarding Claim 40, Thorp discloses one or several strip shaped opening pattern elements are producible and extending up to the edge of the cover lid (Figure 5).
14. Regarding Claim 41, Thorp discloses strip shaped opening pattern elements pass smoothly into the central opening and form pear-shaped opening (Figure 5).
15. Regarding Claim 42, Thorp discloses two strip-shaped opening pattern elements which are producible and located opposite each other (Figure 5).
16. Regarding Claim 43, Thorp discloses small circular openings which are producible in the cover lid in addition to the central opening and which surround the center opening (Figure 2).
17. Regarding Claim 44, Thorp discloses that severing the lid portion elements causes an irreversible elimination of the material bond along the predetermined breaking locations 59 (Figure 5).
18. Regarding Claim 45, Thorp discloses a can body 12 (Figure 1) which is a deep drawn cup of aluminum (Column 2, Lines 33-34).
19. Regarding Claim 51, Thorp discloses a fuel can 10 (Figure 1) with a can body 12 (Figure 1) containing a fuel filling 32 (Figure 2) and cover lid 16 (Figure 1) which is formed by a sealing foil which by sealing onto a flange like rim 22 (Figure 2) of the can body is firmly connected to the can body, wherein the cover lid is designed in such a manner that at least one opening (Figure 3) in the cover lid is producible by a complete or partial severing or detaching of one or more lid portion elements along one or several material bonded predetermined breaking locations. Thorp does not disclose at least two aluminum foils, which are interconnected with each other by a polyethylene layer

wherein a first one of the two metal foils is weakened or interrupted along the predetermined breaking location whereas the second metal foil is continuous in the area of the predetermined breaking location whereas the second metal foil is continuous in the area of the predetermined breaking location and faces the can body and wherein after the complete severing of the predetermined breaking locations, the severable lid portion elements remain undetachably connected at the cover lid. However, Jacke teaches at least two aluminum foils 30/31 (Figure 3), which are interconnected with each other by a polyethylene layer 32 (Figure 3; Column 3, Lines 5-8) wherein a first one of the two metal foils is weakened or interrupted 42 (Figure 3) along the predetermined breaking location whereas the second metal foil 30 (Figure 3) is continuous in the area of the predetermined breaking location whereas the second metal foil is continuous in the area of the predetermined breaking location and faces the can body (Figure 3) and wherein after the complete severing of the predetermined breaking locations, the severable lid portion elements remain undetachably connected at the cover lid (Figure 3). Therefore, it would have been obvious for one of ordinary skill in the art at the time the invention was made to modify Thorp to include two aluminum foils interconnected by a polyethylene layer where the first metal foil is weakened along a predetermined breaking location whereas the second metal foil is continuous in the area of the predetermined breaking location and the second metal foil faces the can body, as taught by Jacke, in order to strengthen the cover lid while still allowing the tab to be easily removed.

20. Regarding Claim 52, Thorp discloses a fuel can 10 (Figure 1) with a can body 12 (Figure 1) containing a fuel filling 32 (Figure 2) and cover lid 16 (Figure 1) which is formed by a sealing foil which by sealing onto a flange like rim 22 (Figure 2) of the can body is firmly connected to the can body, wherein the cover lid is designed in such a manner that at least one opening (Figure 3) in the cover lid is producible by a complete or partial severing or detaching of one or more lid portion elements along one or several material bonded predetermined breaking locations. Thorp does not disclose at least two aluminum foils, which are interconnected with each other by a polyethylene layer wherein a first one of the two metal foils is weakened or interrupted along the predetermined breaking location whereas the second metal foil is continuous in the area of the predetermined breaking location whereas the second metal foil is continuous in the area of the predetermined breaking location and faces the can body and wherein the cover lid is designed in such a manner that by severing one or several lid portion elements, various openings are selectively producible in the cover lid. However, Jacke teaches at least two aluminum foils 30/31 (Figure 3), which are interconnected with each other by a polyethylene layer 32 (Figure 3; Column 3 Lines 5-8) wherein a first one of the two metal foils is weakened or interrupted 42 (Figure 3) along the predetermined breaking location whereas the second metal foil 30 (Figure 1) is continuous in the area of the predetermined breaking location whereas the second metal foil is continuous in the area of the predetermined breaking location and faces the can body (Figure 3) and wherein the cover lid is designed in such a manner that by severing one or several lid portion elements, various openings are selectively producible in the cover lid (Figure

14). Therefore, it would have been obvious for one of ordinary skill in the art at the time the invention was made to modify Thorp to include two aluminum foils interconnected by a polyethylene layer wherein the first metal foil is weakened along a predetermined breaking location whereas the second metal foil is continuous in the area of the predetermined breaking location and the second metal foil faces the can body, as taught by Jacke, in order to strengthen the cover lid while still allowing the tab to be easily removed.

21. Regarding Claim 53, Thorp discloses a fuel can 10 (Figure 1) with a can body 12 (Figure 1) containing a fuel filling 32 (Figure 2) and cover lid 16 (Figure 1) which is formed by a sealing foil which by sealing onto a flange like rim 22 (Figure 2) of the can body is firmly connected to the can body, wherein the cover lid is designed in such a manner that at least one opening (Figure 3) in the cover lid is producible by a complete or partial severing or detaching of one or more lid portion elements along one or several material bonded predetermined breaking locations. Thorp does not disclose at least two aluminum foils, which are interconnected with each other by a polyethylene layer wherein a first one of the two metal foils is weakened or interrupted along the predetermined breaking location whereas the second metal foil is continuous in the area of the predetermined breaking location whereas the second metal foil is continuous in the area of the predetermined breaking location and faces the can body and wherein the cover lid is designed in such a manner that by the severing of the lid portion elements a center opening, which has substantially the same shape as the surface of a fuel filling in the can body at a medium level of fill and is concentrically arranged relative

to same, and one or several strip-shaped opening patten elements, which are extending radially outwards from same, in particular up to the edge of the cover lid, and smoothly pass into the central opening, are producible in the cover lid. However, Jacke teaches at least two aluminum foils 30/31 (Figure 3), which are interconnected with each other by a polyethylene layer 32 (Figure 3; Column 3, Lines 5-8) wherein a first one of the two metal foils is weakened or interrupted 42 (Figure 3) along the predetermined breaking location whereas the second metal foil 30 (Figure 3) is continuous in the area of the predetermined breaking location whereas the second metal foil is continuous in the area of the predetermined breaking location and faces the can body (Figure 3) and wherein the cover lid is designed in such a manner that by the severing of the lid portion elements a center opening (Figure 5), which has substantially the same shape as the surface of a fuel filling in the can body at a medium level of fill and is concentrically arranged relative to same, and one or several strip-shaped opening pattern elements, which are extending radially outwards from same, in particular up to the edge of the cover lid, and smoothly pass into the central opening, are producible in the cover lid (Figure 14). Therefore, it would have been obvious for one of ordinary skill in the art at the time the invention was made to modify Thorp to include two aluminum foils interconnected by a polyethylene layer wherein the first metal foil is weakened along a predetermined breaking location whereas the second metal foil is continuous in the area of the predetermined breaking location and the second metal foil faces the can body, as taught by Jacke, in order to strengthen the cover lid while still allowing the tab to be easily removed.

22. Regarding Claims 54 and 55, Thorp teaches all the limitations substantially as claimed except for a sealing foil comprising a predetermined breaking location and in addition to the sealing layer at least two metal foils interconnected by a synthetic material layer located between same, of which a first one is weakened along the predetermined breaking location and in particular, wherein the metal foils are aluminum foils and are interconnected through a polyethylene layer and fuel tight. However, Jacke teaches a sealing foil 20 (Figure 1) comprising a predetermined breaking location and in addition to the sealing layer at least two metal foils 30/31 (Figure 3) interconnected by a synthetic material layer 32 (Figure 3) located between same, of which a first one is weakened along the predetermined breaking location and a second one is preferably continuous and in particular, wherein the metal foils are aluminum foils (Column 7, Lines 21-23) and are interconnected through a polyethylene layer (Column 3, Lines 5-8). Therefore, it would have been obvious for one of ordinary skill in the art at the time the invention was made to modify Thorp to include a sealing foil comprising a predetermined breaking location and in addition to the sealing layer at least two metal foils interconnected by a synthetic material layer located between same, of which a first one is weakened along the predetermined breaking location and a second one is preferably continuous and in particular, wherein the metal foils are aluminum foils and are interconnected through a polyethylene layer, as taught by Jacke, in order to strengthen the cover lid while still allowing the foil to be easily removed.
23. Regarding Claim 56, Thorp discloses a use fuel can as a thermal, heat or light source (Figure 1).

24. Claims 46-48 and 50 are rejected under 35 U.S.C. 103(a) as being unpatentable over Thorp (U.S. Patent No. 3,701,454) in view of Jacke (U.S. Patent No. 3,435,977) and Mansnerus et al. (U.S. Patent No. 3,811,817).

25. Regarding Claims 46-48 and 50, Thorp and Jacke teach all the limitations substantially as claimed except for a fuel filling consisting of methanol or polyethylene glycols and a wick of a cotton or fleece like material. However, Mansnerus et al. teaches a fuel filling consisting of methanol (Column 3, Line 8) or polyethylene glycols (Column 4, Lines 1-2) and a wick 14 (Figure 1) of a cotton or fleece like material. Therefore, it would have been obvious for one of ordinary skill in the art at the time the invention was made to modify Thorp and Jacke to include a fuel filling consisting of methanol or polyethylene glycols and a wick of a cotton or fleece like material, as taught by Mansnerus et al., in order to provide the appropriate fuel for the container.

26. Claims 48 and 49 are rejected under 35 U.S.C. 103(a) as being unpatentable over Thorp (U.S. Patent No. 3,701,454) in view of Jacke (U.S. Patent No. 3,435,977) and Hoffmann (U.S. Patent No. 6,592,363).

27. Regarding Claims 48 and 49, Thorp and Jacke teach all the limitations substantially as claimed except for a wick of a cotton or fleece like material and a diethylene glycol fuel. However, Hoffmann teaches a wick 50 (Figure 1) of a cotton or fleece like material and a diethylene glycol fuel (Column 4, Lines 11-12). Therefore, it would have been obvious for one of ordinary skill in the art at the time the invention was made to modify Thorp and Jacke to include a wick of a cotton or fleece like material and

a diethylene glycol fuel, as taught by Hoffmann, in order to provide the appropriate fuel for the container.

28. Applicant is duly reminded that a complete response must satisfy the requirements of 37 C.F. R. 1.111, including: "The reply must present arguments pointing out the specific distinctions believed to render the claims, including any newly presented claims, patentable over any applied references. A general allegation that the claims "define a patentable invention" without specifically pointing out how the language of the claims patentably distinguishes them from the references does not comply with the requirements of this section. Moreover, "The prompt development of a clear issue requires that the replies of the applicant meet the objections to and rejections of the claims." Applicant should also specifically point out the support for any amendments made to the disclosure. See MPEP 2163.06 II(A), MPEP 2163.06 and MPEP 714.02. The "disclosure" includes the claims, the specification and the drawings.

Response to Arguments

29. Applicant's arguments filed June 11, 2009 have been fully considered but they are not persuasive.

30. Applicant argues that neither Thorp nor Jacke relate to a fuel can/and or disclose sealing foils. However, Thorp discloses a can which can hold fuel and Jacke teaches aluminum-PE-aluminum layers which are considered foils since they are thin layers of material.

31. Applicant argues that their invention is aimed "to directly use the fuel can without removing/dispensing the content". However, Applicant is arguing more than that which is claimed. The claims don't require the cover lid to be permanent or non-removable.

32. Applicant argues that Mansnerus discloses liquid fuels and not solid, paste or pseudo-solid fuels. However, these are known types of fuel and are art accepted equivalents for use in different environments (ex. camping, boating, etc.).

Conclusion

33. **THIS ACTION IS MADE FINAL.** Applicant is reminded of the extension of time policy as set forth in 37 CFR 1.136(a).

A shortened statutory period for reply to this final action is set to expire **THREE MONTHS** from the mailing date of this action. In the event a first reply is filed within **TWO MONTHS** of the mailing date of this final action and the advisory action is not mailed until after the end of the **THREE-MONTH** shortened statutory period, then the shortened statutory period will expire on the date the advisory action is mailed, and any extension fee pursuant to 37 CFR 1.136(a) will be calculated from the mailing date of the advisory action. In no event, however, will the statutory period for reply expire later than **SIX MONTHS** from the mailing date of this final action.

Any inquiry concerning this communication or earlier communications from the examiner should be directed to **ELIZABETH VOLZ** whose telephone number is (571) 270-5430. The examiner can normally be reached on Monday-Thursday, 8am-5pm EST.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Anthony Stashick can be reached on (571) 272-4561. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

/E. V./
Examiner, Art Unit 3781

/Anthony Stashick/
Supervisory Patent Examiner, Art
Unit 3781